

# FLEX-SLEEVE

## Specifications

Part No.	Color	Gauge	Pipe sizes	Feet per roll	Package Qty.
#100	Black	.4 Mil.	1/2"-1"	200'	20
#101	Orange	.4 Mil.	1/2"-1"	200'	20
#102	Blue	.4 Mil.	1/2"-1"	200'	20
#103	Clear	.4 Mil.	1/2"-1"	200'	20
#104	Red	.4 Mil.	1/2"-1"	200'	20
#108	Black	.4 Mil.	1 1/4"-2"	250'	12
#108B	Blue	.4 Mil.	1 1/4"-2"	250'	12
#108C	Clear	.4 Mil.	1 1/4"-2"	250'	12
#108R	Red	.4 Mil.	1 1/4"-2"	250'	12
#106	Clear	.4 Mil.	3"	1500'	1
#107	Clear	.4 Mil.	4"	1500'	1
#109	Clear	.4 Mil.	5"	1500'	1
#111	Clear	.4 Mil.	6"	1500'	1
#114	Clear	.4 Mil.	8"	1350'	1
#118	Clear	.4 Mil.	10"	1200'	1

# PRECUT FLEX-SLEEVE

## Specifications

Part No.	Color	Gauge	Pipe sizes	Size	Package Qty.
#101C	Orange	.4 Mil.	1/2"-1"	80 pieces cut to 30"	20
#102C	Blue	.4 Mil.	1/2"-1"	80 pieces cut to 30"	20

# FLEX-SLEEVE PRODUCT DATA CHART

Typical properties for 1.0 mil

PROPERTIES	UNITS	ASTM
Density	0.925-.0930 gms/cc	D1505
Melt Index	1.5-2.5 gms/10 min	D1238
Haze	8-12%	D1003
Gloss at 45 degrees	60-70	D2457
COF	.1-.15	D1894
Yield	30,000 sq in/lb	
MVTR	1.0 gms	E96
GTR	400-600 cc	D1434
Resin	FDA Approved	
Tensile Ultimate	MD: 4400 psi	D882
	TD: 4000 psi	D882
Elongation Ultimate	MD: 500%	D882
	TD: 600%	D882
Elemedorf Tear Strength	MD: 230 gms	D1922
	TD: 900 gms	D1922