

FLEX-WRAP

Specifications

Part No.	Dimesions	Package Qty.	Comments
#11	3/32" X 6" X 200'	6 rolls per bag UPS customers ship 5 rolls to a bag	Most Common
#12	3/32" X 6" X 600'	10 rolls per bag	
#18	3/32" X 8" X 200'	4 rolls per bag	

FLEX-WRAP

Specifications

Part No.	Dimesions	Package Qty.	Comments
#204	1/4" X 4" X 50'	7 rolls per bag	
#206	1/4" X 6" X 50'	5 rolls per bag	
#208	1/4" X 8" X 50'	4 rolls per bag	Most Common

FLEX-WRAP PRODUCT DATA CHART

PROPERTIES	UNITS	VALUE	TEST METHOD
Density	lbs/ft3	1.0-1.2	Gravimetric
Tensile strength	psi	MD: 60-100 CD: 30-60	D-828-60
Elongation	per cent	60-120	D-828-60
Compression strength at 10% deflection	psi	4-7	D-1621
Water Vapor Trans.	perm-in.	0.1-0.2	C-355
Water absorption	% by volume (96 hrs)	0.3	D2842
Co-efficient of linear expansion	10 in/in/ F	2.3	D-696
Thermal conductivity	BTU/sq.ft./hr/ F/in	0.26-0.30	D-2396
Maximum temp. service	F	160-180	---
Dielectric constant	at 1.0 kc	1.05	D-1673
Dissipation factor	at 28 C X 1.0 kc	2.0 X 10	---
Co-efficient of thermal conductivity	BTU/hr/FA / F/in	0.28 kc	---
Flammability	AEB, in/ATB, sec	3.0/55	D-16929